

SEALS FOR AIR FILTERS

Field of the Invention

The present invention is directed to seals for air filters.

More particularly, the present invention is directed to air filters for internal combustion engines having a lip seal which fits around an air outlet pipe.

Background of the Invention

Heavy duty air filters used with internal combustion engines for trucks and relatively large earth moving equipment and construction equipment currently use lip seals to seal around air outlet pipes through which filtered engine air is conveyed for combustion. In accordance with the current design, an encapsulated rubber end cap has a radial seal portion thereon engaging the outlet pipe. Material costs for current designs are relatively high and manufacturing complications are introduced because the seal and end caps are unitary, made entirely of polyurethane and are both rather soft. Additional manufacturing complications are introduced because the seal area must be cleaned to remove plastisol and other debris, and because silicone grease is applied so that the soft seal will slide over an outlet pipe of the housing in which the filter is mounted. Since both the seal and end cap are made of polyurethane, both are soft. It is desirable to reduce manufacturing costs and complications and to have a seal and end cap configuration which is more robust.

Summary of the Invention

The present invention is directed to an air filter comprising an annular filter element having an annular filter media with first and second ends closed by first

0396608 113001
FOOTER 80886650

and second annular end caps. A gasket is seated within the first end of the filter media in an initial snap fit with the first end cap. The gasket comprises a unitary body of resilient material having a radially extending flange portion for overlying a radially extending portion of the end cap and has an axially extending body portion. An annular outwardly facing groove in the axially extending body portion of the unitary body receives the axially extending portion of the end cap therein to thereby provide mechanical locking of the gasket on the end cap. An internally facing sealing surface is provided on the axially extending body portion for engaging an air inlet pipe and a tapered portion on the unitary body extends from the groove in a direction away from the radial flange for facilitating insertion of the gasket within the first end of the filter media.

In a further aspect of the invention, the gasket is made of rubber, foam rubber or polyurethane, and in still another aspect of the invention, the gasket is secured by adhesive after it is snap-fitted within the first end of the filter element.

Brief Description of the Drawings

Fig. 1 is a side elevation of an air filter configured in accordance with the principles of the present invention;

Fig. 2 is a side elevation of an annular gasket positioned for insertion into an end cap of a filter in accordance with the present invention;

Fig. 3 is a side elevation showing the gasket snap-fitted to the end cap;

Fig. 4 is an end view of the end cap shown in Figs. 2 and 3, and

Fig. 5 is an end view of the closed end of the filter of Fig. 1.

Detailed Description

Referring now to Fig. 1, there is shown air filter 10 configured in accordance with the principles of the present invention. The air filter includes filter element 12 that is comprised of annular pleated filter media 14 with a hollow core 15 that is disposed between an inner perforated liner 16 made of expanded metal and an outer perforated liner 18 also made of expanded metal. A first metal end cap 20 is fixed over the first end 22 of filter media 14 while a second metal end cap 24 is fixed over a second end 26 of the filter media in order to seal the ends of the filter media so that air does not flow in an axial direction through the filter media. A preferred material for the metal end plates 20 and 24 is a galvanized steel such as GALVANEL®, however any metal or hard plastic may be used. The first and second ends 22 and 26, of the filter media 14 also correspond to the first and second ends of the filter element 12 itself.

Filter element 12 has a gasket 30 configured in accordance with the present invention disposed at its first end 22 for receiving an air outlet pipe 32 through an opening 34 defined by an inwardly facing surface 36 of the gasket 30. The air outlet pipe 32 communicates with the hollow core 15 of the filter media 14 and projects from an end wall 38 of a filter housing 40 (shown in dotted lines) which surrounds the air filter 10 and provides an annular space 41 which receives input combustion air in accordance with standard practice.

The second end 26, of the filter element 12 is closed by a circular end plate 50 (see also Fig. 5). End plate 50 is bonded to end cap 24 and includes a loop 56 for extracting the filter 10 from the housing 40 by pulling the filter 10 off the air outlet pipe 30. A gasket 57 is disposed over the outer surface of the end plate

THE
NEW
YORK
PUBLIC
LIBRARY

the piece from the end cap 20 and is
gasket 30
the end cap is preferably made of a

THE UNIVERSITY OF CHICAGO

[illegible][illegible]